



## FCC series

Unit Model		Indoor	FCC-24	FCC-30	FCC-36	FCC-44	
Outdoor		FSG-24	FSG-30	FSG-36	FSGD-44		
Nominal Cooling Capacity	Btu/Hr.		24000	30000	36000	44000	
	Kw.		7.03	8.79	10.55	12.9	
Nominal Heating Capacity	Btu/Hr.		24500	30600	36650	44500	
	Kw.		7.18	8.97	10.74	13.04	
Nominal Air Circulation	CFM.		900	940	970	1050	
	L/S.		424.76	443.63	457.79	495.55	
INDOOR UNIT	Fan Motor Type	Permanent Split Capacitor					
	Operation Control Type	Wireless Controller					
	<b>Unit Dimension</b>						
	Height	mm.	290	290	290	290	
	Depth	mm.	820	820	820	820	
Width	mm.	840	840	840	840		
OUTDOOR UNIT	Compressor Type		Rotary		Scroll		
	Power Input	Kw.	1.93	2.64	3.01	4.81	
	Fan Motor Type	Permanent Split Capacitor					
	Fan Blade Diameter	Inc.	18	20	20	18	
	<b>Unit Dimension</b>						
	Height	mm.	610	676	676	1156	
	Width	mm.	834	970	970	970	
Depth	mm.	308	367	367	360		
Refrigerant Type	410A						
Power Supply	Single phase			Three phase			
<b>Piping Size</b>							
Suction	Inc. OD	5/8	5/8	5/8	3/4		
Liquid	Inc. OD	3/8	3/8	3/8	1/2		