



## FG Series

Unit Model	Indoor	FG-12	FG-18	FG-24	FG-30	FG-36	FG-44	FG-56	FG-60	
	Outdoor	FSG-12	FSG-18	FSG-24	FSG-30	FSG-36	FSGD-44	FSGD-56	FSGD-60	
Nominal Cooling Capacity	Btu/Hr.	12000	18000	24000	30000	36000	44000	56000	60000	
	Kw.	3.52	5.28	7.03	8.79	10.55	12.9	16.41	17.58	
Nominal Heating Capacity	Btu/Hr.	12500	18500	24600	30700	36850	45000	56950	61050	
	Kw.	3.66	5.42	7.21	9	10.8	13.19	16.69	17.89	
Nominal Air Circulation	CFM.	400	620	850	1000	1200	1400	1600	1750	
	L/S.	188.78	292.61	401.16	471.95	566.34	660.73	755.12	825.91	
INDOOR UNIT	Fan Motor Type	Permanent Split Capacitor								
	Type	Wireless Controller								
	<b>Unit Dimension</b>									
	Height	mm.	601	601	601	601	601	601	601	601
	Width	mm.	975	975	1276	1276	1564	1877	1877	1877
Depth	mm.	232	232	232	232	232	232	232	232	
OUTDOOR UNIT	Compressor Type	Rotary				Scroll				
	Fan Motor Type	Permanent Split Capacitor								
	Diameter	Inc.	18	18	18	20	20	18	18	18
	<b>Unit Dimension</b>									
	Height	mm.	550	610	610	676	676	1156	1156	1156
	Width	mm.	770	834	834	970	970	970	970	970
Depth	mm.	280	308	308	367	367	360	360	360	
INDOOR UNIT	Refrigerant Type	410A								
	Power Supply	Single phase				Three phase				
	<b>Piping Size</b>									
	Suction	Inc. OD	3/8	5/8	5/8	5/8	5/8	3/4	3/4	3/4
Liquid	Inc. OD	1/4	3/8	3/8	3/8	3/8	1/2	1/2	1/2	