



## FWMF series

	Indoor	FWMF-12	FWMF-18	FWMF-24	FWMF-30	
Unit Model	Outdoor	FSG-12	FSG-18	FSG-24	FSG-30	
Nominal Cooling Capacity	Btu/Hr.	12000	18000	24000	30000	
	Kw.	3.52	5.28	7.03	8.79	
Nominal Heating Capacity	Btu/Hr.	12312	18504	24600	30500	
	Kw.	3.6	15.42	7.21	8.94	
Nominal Air Circulation	CFM.	360	450	600	650	
	L/S.	169.9	212.38	283.17	306.77	
INDOOR UNIT	Fan Motor Type	Permanent Split Capacitor				
	Operation Control Type	Wireless Controller				
	<b>Unit Dimension</b>					
	Height	mm.	270	323	330	330
	Width	mm.	800	1020	1080	1080
Depth	mm.	195	195	230	230	
OUTDOOR UNIT	Compressor Type					
	Power Input	Kw.	1.15	1.5	1.93	2.64
	Fan Motor Type	Permanent Split Capacitor				
	Fan Blade Diameter	Inc.	18	18	18	20
	<b>Unit Dimension</b>					
	Height	mm.	550	610	610	676
	Width	mm.	770	834	834	970
Depth	mm.	280	308	308	367	
Refrigerant Type	410A					
Power Supply	Single phase					
<b>Piping Size</b>						
Suction	Inc. OD	5/8	5/8	5/8	5/8	
Liquid	Inc. OD	3/8	3/8	3/8	3/8	